DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator cantarire SC MIN



Indicator cantarire SC MIN. Producator: Sensocar.

Descriere

WEIGH-TARE-PIECES COUNTER 10000 Divisions
Class III Maximum Certification:
10000 divisions 1µV step 40Ω load (16 load cells of 700Ω)
Additional plug & work hardware
Optimized software with all program optionals embedded
Manual weight adjustment.
Autocalibration without needing new adjustments.
Weighing accumulation and autoaccumulation.
On/Off by key.
Manual tare function.
Piececounter function.
Dynamic and animal weighing dedicated functions.
Discharge function for GROSS-TARE-NET tickets.
Flexible and fully-programmable multirange.
User-definible linearization until 16 points.
Ticket repetition and ticket-per-weighing option.
Data dumping and configuration through PC.
6 selectable languages: Spanish, Portuguese, French, Italian, English and German.
Versions:

- SC MIN/A: Analogic indicator
- SC MIN/BAT12: For external battery 12 V indicator

Basic configuration

· Weight-Tare	
· Pieces Counter	
· Weight accumulations	

· Multirange	
· Communications RS-232 port	
· Compatible protocols	
· Languages	Spanish, English, French, Italian & Portuguese

Software

- Span, fraction and decimals fully customizables.
- Extended accumulation as standard, millions of accumulations with 48-bit totalizer.
- Accumulated Big Total option.
- Scroll, ticket’s header and foot customizables.
- Communication channels Self-testing as standard
- Negative auto-zero as standard to avoid platform’s zero errors
- Proprietary own protocol –S-, For addressable indicator networks (via cable or radio), with
RS232 relay actions, net and gross requests, tare, zero and accumulation actions, battery level, serial number, software version, etc.
-Cost-saving and energy optimization, programmable auto-shutdown time

Optional hardware

- IP-65 protection class against humidity.
- Internal 6V battery.
- External 12V battery.
- Clock, calendar and additional memory.
- Current output for automata.
- Voltage output for automata.
- Second optocoupled serial channel for printer.
- Converts 1st or 2nd RS232 optocoupled channel to RS485.
DSD feature (until 4000 weighings)

Optional

- Customized spcial software.
- Battery level indication (if any).
- Filling by pulse function (litters counting).

Available printers

· LX-300 from EPSON
· SRP 275 from SAMSUNG
· SP298 from STAR
· Otras from pedido

Labelers

· TLP 2844 de ZEBRA

Technical data

Accuracy class	III
Maximum number of verification scale intervals	- 10000
Load cell excitation power supply	8 V DC
Max. signal voltage for dead load	16 mV
Minimum signal voltage for dead load	0 mV
Minimum input voltage per verification scale interval	1µV
Measuring range minimum voltage	8 mV
Measuring range maximum voltage	24 mV
Minimum load cell impedance	40 Ω
Maximum load cell impedance	2000 Ω
Minimum temperature range	-10º C
Maximum temperature range	40º C
Power supply requirements ((option SC MIN/A)	220 V AC
Power supply requirements (option SC MIN/BAT12)	12 V DC
Sense system	Available
Load cell cable length	
4 wire systems	5 m/mm2
6 wire systems	No limit

Cântărirea-TARE 10000 Divizii

Clasa III de certificare maximă 10000 divizii 1µV pas

Sarcină 40Ω (16 celule de sarcină de 700Ω

Plug & hardware suplimentar de lucru

Software-ul optimizat cu toate opționale programului încorporate 19, 40, 60 și 100 de versiuni mm, cu Ultrabright LED.

Reglare manuală greutate

Autocalibrare fără a avea nevoie de noi ajustări.

Cântărire acumulare și autoaccumulation.

ON / OFF cu tasta.

Funcția manual tare.

Funcția Piececounter.

Dinamic și animale de cântărire funcții dedicate.

Funcția de descărcare de gestiune pentru bilete GROSS-TARE-NET.

Multirange flexibil și complet programabile

-Utilizator definible liniarizare până la 16 de puncte.

Repetiție bilet și opțiunea bilet pe-cântărire.

Date de dumping și de configurare prin intermediul PC-ului.

6 limbi selectabile: spaniolă, portugheză, franceză, italiană, engleză și germană.

Versiuni:

- SC4 / A: Visor analógico / Analogic Indicator
- SC4 / D: Indicator celule de sarcină digitală
- SC4 / BAT12: Baterie

Ambele versiuni pot include o baterie externă de 12 V

Coajă INOX 6 cifre 19 mm

Pentru desktop sau pe perete utilizare

Configurația de bază

- Greutate-Tare

- Piese Counter
- Acumulări Greutate
- Multirange
- Comunicatii RS-232 de comunicare portul
- Protocoale compatibile
- Spaniolă, engleză, franceză, italiană și portugheză

Software-ul

- Span, fracțiune și zecimale customizables complet.
- Acumulare Extended standard, milioane de acumulări cu 48 de biți totalizator.
- Acumulat opțiune Big total.
- Scroll, antet și picior customizables bilete de.
- Canalele de comunicare auto-testare standard.
- Negativ auto-zero ca standard, pentru a evita

Hardware opțional

- Clasa IP 65 de protecție împotriva umidității.
- 6V internă a bateriei.
- 12V Externe acumulator.
- Ceas, calendar și memorie suplimentară.
- 2 intrări Optocoupled și 6 ieșiri de releu
- Ieșire de curent pentru automate.
- Ieșire de tensiune pentru automate.
- Optocoupled al doilea canal serial pentru imprimantă
- Convertește 1 sau 2 RS232 optocoupled canal la RS485.
- Convertește 1 sau 2 canale RS232 la RF
- Bibascule
- Caracteristica DSD (până 4000 cântăriri)

Imprimante disponibile

- DPU 414 de SEIKO
- LX-300 de la Epson
- SRP 270 de la Samsung
- SP298 de la STAR
- TM295 de la Epson

Etichetatoare

- T402 de la ZEBRA
- EZ4TT din C.ITOH

date tehnice

Clasa de precizie III

Numărul maxim de verificare a scalei intervale -10000

Încărcați excitație celule de alimentare cu energie 8 V DC

Max. tensiune de semnal pentru sarcină mort 16 mV

Tensiune minimă de semnal pentru sarcină mort 0 mV

Tensiune minimă de intrare pe Interval de verificare 1 µV

Interval de măsurare de tensiune minimă 8 mV

Interval de măsurare de tensiune maximă de 24 mV

Impedanta de celule de sarcină minim 40 Ω

Impedanta de celule de sarcină maximă 2000 Ω

Interval minim de temperatură -10º C

Gama de temperatura maximă 40 ° C

Cerințe de alimentare (opțiuni SC1 / A sau SC1 / D) 220 V AC

Cerințe de alimentare (SC1 / BAT12) 12 V DC

Sistemul Sense Disponibil

Lungime cablu de încărcare de celule 4 sisteme de sârmă 5 m / mm2 6 sisteme de sârmă No Limit