DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Afisaj repetitor REP19



Afisaj repetitor REP19. Producator: Sensocar.

Descriere

WEIGH-TARE-PIECES COUNTER 10000 Divisions

Class III Maximum Certification 10000 divisions 1µV step 40Ω load (16 load cells of 700Ω

Additional plug & work hardware

Optimized software with all program optionals embedded 19, 40, 60 and 100 mm versions, with ultrabright LED.

Manual weight adjustment

Autocalibration without needing new adjustments.

Weighing accumulation and autoaccumulation.

On/Off by key.

Manual tare function.

Piececounter function.

Dynamic and animal weighing dedicated functions.

Discharge function for GROSS-TARE-NET tickets.

Flexible and fully-programmable multirange

User-definible linearization until 16 points.

Ticket repetition and ticket-per-weighing option.

Data dumping and configuration through PC.

6 selectable languages: Spanish, Portuguese, French, Italian, English and German.

Versions

- SC 1/A: Analogic indicator
- SC 1/D: Digital load cells indicator
- SC 1/BAT6: Internal 6 V battery indicator
- SC 1/BAT12: For external battery 12 V indicator
- SC 1/RELES: 4 to 6 relay output
- SC 1/REP: Repeater indicator
- SC 1/4-20 ó SC1/0-10: 4-20 mA / 0-10 V analogic output
- SC 1/IP65: Protected against humidity IP-65
- SC 1/RS: RS-232/485 optocoupled output

REP INT RANGE

- Intelligent repeaters with adapted communication protocols for the connection to commercial indicators of

different manufacturers

REP RANGE

- Low cost repeaters with “Sensocar” internal bus

Basic configuration

· Weight-Tare	
· Pieces Counter	
· Intelligent Repeater	
· Communications	
- Radio	
- Compatible protocols	
· Languages	Spanish, English, French, Italian & Portuguese

Optional hardware

- IP-65 protection class against humidity.
- Internal 6V battery.
- External 12V battery.
- Clock, calendar and additional memory.
- 2 Optocoupled inputs and 6 relay outputs
- Current output for automata.
- Voltage output for automata.
- Second optocoupled serial channel for printer
- Converts 1st or 2nd RS232 optocoupled channel to RS485.
- Converts 1st or 2nd RS232 channel to RF
- Bibascule
- DSD feature (until 4000 weighings)

GAMA 19 mm

Cantarire TARE piese COUNTER 10000 Divizii

Clasa III de certificare maximă 10000 divizii 1µV pas Sarcină 40Ω (16 celule de sarcină de 700Ω Plug & hardware suplimentar de lucru Software-ul optimizat cu toate opționale programului încorporate 19, 40, 60 și 100 de versiuni mm, cu Ultrabright LED. Reglare manuală greutate Autocalibrare fără a avea nevoie de noi ajustări. Cântărire acumulare și autoaccumulation. ON / OFF cu tasta. Funcția manual tare. Funcția Piececounter. Dinamic și animale de cântărire funcții dedicate. Funcția de descărcare de gestiune pentru bilete GROSS-TARE-NET. Multirange flexibil și complet programabile -Utilizator definible liniarizare până la 16 de puncte. Repetiție bilet și opțiunea bilet pe-cântărire. Date de dumping și de configurare prin intermediul PC-ului. 6 limbi selectabile: spaniolă, portugheză, franceză, italiană, engleză și germană.

Versiuni · SC 1 / A: indicator analogic · SC 1 / D: Indicator celule de sarcină digitală · SC 1 / BAT6: Internal indicator 6 V baterie · SC 1 / BAT12: Pentru baterie externă de 12 V Indicator · SC 1 / Reles: 4-6 releu · SC 1 / REP: indicator Repeater · SC 1 / 4-20 Ó SC1 / 0-10: 4-20 mA / 0-10 V ieșire analogic · SC 1 / IP65: Protecție împotriva umidității IP-65 · SC 1 / RS: RS-232/485 ieșire optocoupled

REP INT RANGE

· Repetoare inteligente cu protocoale de comunicare adaptate pentru conectarea la indicatorii comerciale de la diferiți producători

REP RANGE

· Repetoare low cost cu autobuzul intern "Sensocar"

Configurația de bază · Greutate-Tare · Piese Counter · Repeater inteligent · Comunicații - Radio - protocoale compatibile · Spaniolă, engleză, franceză, italiană și portugheză

Hardware opțional - Clasa IP 65 de protecție împotriva umidității. - 6V internă a bateriei. - 12V Externe

acumulator. - Ceas, calendar și memorie suplimentară. - 2 intrări Optocoupled și 6 ieșiri de releu - Ieșire de curent pentru automate. - Ieșire de tensiune pentru automate. - Optocoupled al doilea canal serial pentru imprimantă - Convertește 1 sau 2 RS232 optocoupled canal la RS485. - Convertește 1 sau 2 canale RS232 la RF - Bibascule - Caracteristica DSD (până 4000 cântăriri)