DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator de cantarire W200



Indicator de cantarire W200. Producator: Laumas.

Descriere

- Possible installations: panel, wall
- Multiprogram: single loading/unloading and multi-product batchings, max 99 formulas
- Six-digit red LED display, 14 mm height
- RS232 and RS485 ports (Modbus RTU/Laumas ASCII protocol)
- 3 logic inputs, 5 relay outputs
- OIML R76:2006 approved, class III, 10000 divis. 0.2µV/VSI
- OIML R61 approved - WELMEC Guide 8.8:2011 (M.I.D.)
- Optional fieldbuses: Profibus DP, DeviceNet, CANopen, Profinet IO, Modbus/TCP, Ethernet/IP. Ethernet TCP/IP port for remote management via internet from PC, smartphone or tablet, etc.
- A/D converter 24bit (16000000 points) 4.8 kHz
- Display range 999999

Some optional features:

- Data storage on USB pen drive
- Box versions: IP67, IP67 ATEX II 3GD, IP64
- ADPEW200: ATEX II 2(1) GD explosion proof box version
- 16-bit Analog output: 0/4-20 mA; 0-5/10 V; ±5/10 V