DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Indicator cantarire LD-SERIAL RS232 & RS485



Indicator cantarire LD-SERIAL RS232 & RS485 Producator: LCM Systems LD-SERIAL RS232 & RS485 Input Large Digit Slave Display

Descriere

LD-SERIAL RS232 & RS485 Input Large Digit Slave Display

Features :

- RS485 Digital Input
- Digit heights 57, 102, 150, 200, 300 or 400mm
- Viewing distances from 25, 50, 75, 100, 140 or 200 metres
- Suspension, panel or wall mounting options
- AC or DC powered versions
- Wide choice of analogue, relay or digital outputs
- IP65 sealed

The LD-SERIAL is a large digit display, used as a slave display with connection by RS232 or RS485.

It can be used to interface with various products available from LCM Systems including; LCA15, ADW15, SMW, T24-SO, MAX etc.

Various options are available including, 4 or 6 digit versions, different height digits allowing viewing from up to 200 metres, DC or AC powering and different mounting options.

The digit heights that are available include 57mm (25m viewing distance), 102mm (50m viewing distance), 150mm (75m viewing distance), 200mm (100m viewing distance), 300mm (140m viewing distance) and 400mm (200m viewing distance).

Mounting options available include Panel Mounting, Suspension Mounting (from top of display) and Wall Mounting (from bottom of display).

Power supply options available include 95-265vac, 11-30vdc and 48vac.

Output options available include 4-20mA, 0-10v, ±10v, 2 relay alarms, 4 relay alarms, RS232 or RS485.

The main application for the LD-STRAIN is for simple crane weighing applications, hoist and winch monitoring etc. The various output options available allow for the re-transmission of the display signal or for process control.

Different input signals are available including Load Cell/Strain Gauge input (see LD-STRAIN), process input (see LD-PROCESS) or wireless version (see LD-WIRELESS). LCM Systems engineers will be pleased to discuss your specific application requirements with you. They will be able to advise on the correct product selection, options required and advise on suitable sensors, where required.

Specifications	
Power Supply	95-265vac Optional 11-30vdc or 48vac
Power Rating	40 watts maximum

Input Signals	RS232 (with S2 input option) RS485 and RS422 (with S4 input option)
Display Range	4 digit version: -1999 to 9999 6 digit version: -199999 to 999999
Connections	All user/installation connections using detachable field screw terminals
Case Material	Heavy Duty PVC
Storage Temperature	-20 to +70°C
Operating Temperature	0 to +50°C (internal heater option to allow operation to -25°C)
Environmental Sealing	IP65

Specifications