DATA SPEED S.R.L.
Str. Corneliu Coposu nr. 103, Cluj-Napoca, cod 400235, jud. Cluj
Tel: 0264 566 473, 0735 803 121
office@dataspeed.ro · www.dataspeed.ro

Dispozitiv testare cuplu DB



Dispozitiv testare cuplu DB Producator: Kern Capacitate: 1kg, 5kg, 10kg, 20kg, 50kg, 100kg, 200kg, 500kg

Descriere

- Particularly suitable for testing torque wrenches, electric hand screwdrivers and cordless screwdrivers
- Rotary sensor for dynamic testing of electric screwdrivers
- Metal housing for durable usage in harsh environmental conditions
- Capacity display: A bar lights up to show how much of the measuring range is still available
- Back-lit LCD graphic display
- num/1] Rubber feet with anti-slip feature with SAUTER DB 0.5-4 to DB 10-3
- Robust mounting plate for secure fixing with SAUTER DB 20-3 to DB 50-2
- Scope of supply: mounting plate, sturdy carry case
- Internal data memory saves up to 500 measurements. The content of the memory can be transferred to the PC using optional software
- USB and RS 232 data interfaces to the PC included
- Peak Hold Mode to capture peaks
- Can be used in both directions of rotation
- Function to set limits, programming of Max./Min., in pull and push direction, with output of audible and optical signal. Ideal mode for efficient and accurate testing of standard parts
- AUTO-OFF function to preserve the battery

[d] g

Deosebit de potrivit pentru chei de testare de cuplu, șurubelnițe de mână electrice și șurubelnițe cu acumulator

Senzor rotativ pentru testarea dinamică a surubelnite electrice

Carcasă metalică pentru utilizarea durabilă în condiții dure de mediu

Capacitate de afișare: O bară se aprinde pentru a arăta cât de mult a domeniului de măsurare este încă disponibil

LCD luminat afișaj grafic

Num / 1] Picioare din cauciuc cu caracteristica anti-alunecare cu SAUTER DB 0,5-4 DB 10-3

Placă de montare robustă pentru fixarea sigură cu SAUTER DB 20-3 la DB 50-2

Domeniul de aplicare de alimentare: placă de montaj, Geantă de transport robust

Memoria internă de date economisește până la 500 de măsurători. Conținutul memoriei poate fi transferată la PC utilizând software-ul opțional

USB și RS 232 de date interfețe cu PC-ul inclus

Modul Hold de vârf pentru a captura vârfuri

Poate fi utilizat în ambele sensuri de rotație

Funcția de a stabili limite, programarea max./min., În direcția de tragere și împingere, cu ieșire de semnal acustic și optic. Modul ideal pentru testarea eficientă și precisă a pieselor standard

Funcția AUTO-OFF pentru a păstra bateria