DINI ARGEO
Scales - Weighing systems

FXC

FXC SERIES BENDING BEAM LOAD CELLS



Bending beam load cells for approved weighing, automatic systems, dosage.

CAPACITIES (kg): 10, 20, 50, 100, 200, 300, 500.

Stainless steel. IP68 protection. C3 precision class.

The best solution
for advanced industrial
applications

MAIN FEATURES

- C3 PRECISION CLASS
- STAINLESS STEEL
- IP68 PROTECTION
- MAX. CAPACITIES FROM 10 TO 500 kg
- SHIELDED CONNECTION CABLE
- OIML CERTIFICATE AVAILABLE UPON REQUEST
- TEST CERTIFICATE AVAILABLE UPON REQUEST


TECHNICAL FEATURES

- Minimum load cell verification interval: Vmin = EMax / 10.000
- Maximum number of verification intervals: nLC= 3000
- Full Scale Output: 2mV/V +/- 0,1%
- Combined error: 0,017% of Full Scale Output (F.S.)
- Non-Repeatability: 0,015% F.S.
- Temperature effect on zero: +/- 0,002% /°C
- Temperature effect on full scale output: +/- 0,0012% /°C
- Compensated Temperature Range: –10°C/+40°C
- Operating Temperature Range: –20°C/+60°C
- Creep error after 30 minutes +/- 0,016% F.S.
- Maximum tolerated excitation voltage: 15 VDC
- Input Resistance: 385 ± 20 Ohm
- Output Resistance: 350 ± 5 Ohm
- Insulation Resistance: > 5000 MOhm
- Safe Overload: 200% F.S.
- Ultimate Overload: 300% F.S.
- Nominal displacement: < 0,4 mm
- 4-wire shielded cable, 3m long, 4mm diameter.

ATEX VERSION

- The CCATEX certificate makes the load cell suitable for use in hazardous areas with protection methods according to:
  ATEX II 1G Ex ia IIC T6 (Ta -20÷+40°C) TX (Ta -20÷+65°C) Ga
  ATEX II 1D Ex ta IIIC TX°C (Ta -20÷+40°C) TX°C (Ta -20÷+65°C) Da IP65.
  The certificate includes the manual and the ATEX CE conformity declaration (available in EN, DE, FR, and IT).
- IMPORTANT: the certificate refers to the single load cell. For systems with more load cells, it is necessary to order one certificate for each load cell.

DETAIL 1



Dimensions (mm)

Wiring Code	
Colour	*Function*
--	SHIELD
BLACK	OUTPUT +
RED	INPUT +
BLUE	OUTPUT -
WHITE	INPUT -

VERSIONS

Models Available

Code	Max (kg)
FXC10	10
FXC20	20
FXC50	50
FXC100	100
FXC200	200
FXC300	300
FXC500	500

www.diniargeo.com



DINI ARGEO FRANCE sarl
Nogent-sur-Marne
info.fr@diniargeo.com

DINI ARGEO GMBH
Sinsheim - Germany
info.de@diniargeo.com

DINI ARGEO UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI ARGEO WEIGHING INSTRUMENTS Ltd
Shanghai - China
info.cn@diniargeo.com

DINI ARGEO WEIGHBRIDGES
Calto (RO) – Italy
info@diniargeo.com

DINI ARGEO
Scales - Weighing systems

ATEX

ISO 9001:2008

HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418 Fax. +39.0536 843521
info@diniargeo.com

SERVICE ASSISTANCE
Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784 Fax. +39.0536 926654
service@diniargeo.com

SALES AND TECHNICAL ASSISTANCE SERVICE