DINI ARGEO
Scales - Weighing systems

LCCB

"LCCB": CABLE for CONNECTION TO LOAD CELLS



Shielded cable for connection of weight indicators to load cells or junction boxes.

The best solution
for advanced industrial
applications

LCCB cable features

- Type: 6 x 0,25 mm².
- Built-in shielding for protection from disturbances.

Dini Argeo standard of colour codes	
Colour	*Function*
YELLOW	OUTPUT -
PINK	OUTPUT +
GREEN	SENSE +
WHITE	SENSE -
BROWN	INPUT +
GREY	INPUT -

LCCBM cable features

- Indicated for applications with moving cables.
- Type: 4 x 0,34 mm².
- Built-in shielding for protection from disturbances.

Dini Argeo standard of colour codes	
Colour	*Function*
YELLOW	OUTPUT -
GREEN	OUTPUT +
WHITE	INPUT -
BROWN	INPUT +

DETAIL 1



LCCBM: shielded 4-pole cable for load cells.

www.diniargeo.com



DINI ARGEO FRANCE sarl
Nogent-sur-Marne
info.fr@diniargeo.com

DINI ARGEO GMBH
Sinsheim - Germany
info.de@diniargeo.com

DINI ARGEO UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI ARGEO WEIGHING INSTRUMENTS Ltd
Shanghai - China
info.cn@diniargeo.com

DINI ARGEO WEIGHBRIDGES
Calto (RO) – Italy
info@diniargeo.com

DINI ARGEO
Scales - Weighing systems

ATEX

ISO 9001:2008

HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418 Fax. +39.0536 843521
info@diniargeo.com

SERVICE ASSISTANCE
Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784 Fax. +39.0536 926654
service@diniargeo.com

SALES AND TECHNICAL ASSISTANCE SERVICE