DINI ARGEO
Scales - Weighing systems

LP542S

LP542S DIRECT THERMAL LABELLER



Direct thermal labeller with fitted front peel mechanism with label present sensor; it is connectable to DFW, TRI, 3590, and TRS series' indicators.
The fast label throughput, the high printing resolution and the compact size make it suitable for printing in any industrial environment.

Working in cooperation with:

SC DATA SPEED SRL

STR DONATH N. 115/33 - 400331 - JUD. CLUJ
Tel. 0040-264566473 Fax. 0040-364-815440
office@cantare.com.ro

The best solution
for advanced industrial
applications

TECHNICAL FEATURES

- PRINTING METHOD: Direct thermal.
- PRINTING RESOLUTION: 203 dpi (8 dots/mm).
- PRINT SPEED: up to 127 mm/sec.
- MAXIMUM PRINT LENGTH: 1016 mm.
- MAXIMUM PRINT WIDTH: 108 mm.
- LABEL LENGTH: From 10 mm up to 999 mm.
- LABEL WIDTH: From 20 mm up to 112 mm.
- LABEL THICKNESS: From 0.06 mm up to 0.19 mm.
- LABEL ROLL DIMENSIONS: 127 mm OD (5.0" OD).
- FONTS: 8 fixed alphanumeric fonts, 1 true type Font with rotation at 0, 90, 180, and 270 degrees.
- AVAILABLE BAR CODES: Code 39, Code 39C, Code 93, Code 128uCC, Code 128 (Subset A, B, C), Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN e UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China Post, ITF 14, EAN14.
- AVAILABLE 2D BAR CODES: PDF-417, MAXICODE, DATA MATRIX, QR code.
- MEMORY: 2 MB DRAM, 2 MB Flash Memory.
- INTERFACES: RS 232, Parallel, USB 1.1.
- STANDARD SOFTWARE PROGRAMMING, for the creation of customised labels with logos, images, weight data, and bar codes.
- DIMENSIONS: 240 X 200 X 164 mm.
- POWER SUPPLY: Switching 100/240 VAC, 24V 3.75A DC (external power adapter).
- OPERATING TEMPERATURE: From 5 to 40°C.

DETAIL 1



www.diniargeo.com



DINI ARGEO FRANCE sarl
Nogent-sur-Marne

DINI ARGEO GMBH
Sinsheim - Germany

DINI ARGEO UK Ltd
Taunton - United Kingdom

DINI ARGEO WEIGHING INSTRUMENTS Ltd
Shanghai - China

DINI ARGEO WEIGHBRIDGES
Calto (RO) – Italy

DINI ARGEO
Scales - Weighing systems

HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy

ATEX

ISO 9001:2008

SC DATA SPEED SRL

STR DONATH N. 115/33 - 400331 - JUD. CLUJ

Tel. 0040-264566473 Fax. 0040-364-815440

office@cantare.com.ro

SALES AND TECHNICAL ASSISTANCE SERVICE