DINI ARGEO
Scales - Weighing systems

EPWLI

EPWLI “LOGISTIC” STAINLESS STEEL PALLET-WEIGHING FLOOR SCALES SERIES



Quick and accurate stainless steel pallet weighing scales, easy to use and transport. Integrated extractable weight indicator complete of stretchable connection cable which may be easily positioned according to one's weighing requirements. The automatic multirange capacity allows the maximum accuracy on the lower weight values, mantaining the same load capacity. Available also in dual range APPROVED version, for legal for trade use.

Working in cooperation with:

SC DATA SPEED SRL

STR DONATH N. 115/33 - 400331 - JUD. CLUJ
Tel. 0040-264566473 Fax. 0040-364-815440
office@cantare.com.ro

The best solution
for advanced industrial
applications

MAIN FEATURES

- Weight indicator with support bracket having an adjustable inclination, for use on the column (optional), wall (optional adjustable support) or table.
- Stainless steel IP68 case, easy to clean and resistant in harsh and corrosive environments.
- Waterproof 5-key functional keypad.
- LCD 25mm backlit display with 6 high contrast digits and icons for indication of active functions.
- Functions with 4 shear beam 1000 Ohm stainless steel load cells approved according to OIML R60 C3 standards (3000+3000 divisions), IP68 protection degree, able to handle double the nominal load.
- Sheet-stainless steel structure and load surface, complete of adjustable feet.
- Level, wheels, and transport handle.
- Connection cable to the indicator, 3 m long.
- Accuracy: +/-0,05% of the capacity.
- Digital calibration and Set-Up from keypad or from PC through DINITOOLS.
- Power supply 110-240Vac.

SELECTABLE AND KEYPAD FUNCTIONS

- Clearing; automatic and manual tare, print.
- X 10 High resolution visualisation.
- Net/Gross or lb/kg conversion.
- Accumulation.
- Formula weighing.
- +/- Checkweighing.
- Percentage weighing.
- Alibi, for approved weigh transmission (optional).
- Counting.
- Input/Output.

I/O SECTION:

- RS232/C bidirectional port on RJ connector (or USB optionally) for quick or RS485 connection, configurable for PC, PLC, additional remote display.
- RS232/C bidirectional port for connection to printer or labeller.
- IR input for remote control management.

AVAILABLE ACCESSORIES

- Infrared remote control.
- Support column for indicator.

DIMENSIONS mm

- Values in mm

VERSIONS

Available models

Code	l x w x h (mm)	Max (kg)	d (kg)	CE-M 2x3000e (kg)
EPWLI-1	1260x800x75	600/1500/2000	0,2/0,5/1	-
EPWLIM-1 M	1260x800x75	1000/2000	-	0,5/1

www.diniargeo.com



DINI ARGEO FRANCE sarl
Nogent-sur-Marne

DINI ARGEO GMBH
Sinsheim - Germany

DINI ARGEO UK Ltd
Taunton - United Kingdom

DINI ARGEO WEIGHING INSTRUMENTS Ltd
Shanghai - China

DINI ARGEO WEIGHBRIDGES
Calto (RO) – Italy

DINI ARGEO
Scales - Weighing systems

HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy

ISO 9001:2008

SC DATA SPEED SRL

STR DONATH N. 115/33 - 400331 - JUD. CLUJ

Tel. 0040-264566473 Fax. 0040-364-815440

office@cantare.com.ro

SALES AND TECHNCAL ASSISTANCE SERVICE