Display devices KERN KFE-TM · KFN-TM · KXS-TM



5 KERN KFE-TM

STANDARD

CAL EXT | RECIPE | TOL | MOVE | IP 65 | INOX

STANDARD

ACCU | 230 V | 2 YEARS WARRANTY | 1 DAY

FACTORY

M



6 KERN KFN-TM

STANDARD

CAL EXT | PCS | TOL | MOVE | IP 65 | INOX

STANDARD

230 V | 2 YEARS WARRANTY | 1 DAY

OPTION

RS 232 | ACCU

FACTORY

M



7 KERN KXS-TM

STANDARD

CAL EXT | PCS | RECIPE | PERCENT | TOL | MOVE

STANDARD

IP 68 | INOX | 230 V | 2 YEARS WARRANTY | 1 DAY

OPTION

RS 232 | ACCU | BT

FACTORY

M

KERN evaluation devices for many platforms – innovative technology, to construct your own weighing system. Can be used in any combination, e. g. with all platforms on page 121-123

Features	**Models KERN**		
	5 KFE-TM	**6 KFN-TM**	**7 KXS-TM**
Characteristics	Stainless steel, protected by IP65	Display device made from stainless steel with IP65 protection	Stainless steel display device with integrated power supply
Display (segments)	6 digts	5 + ½ digts	6 digts
EC type approval	yes	–	yes
Resolution verifiable	6.000 e	6.000 e	10.000 e
Resolution non verifiable	30.000 d	30.000 d	30.000 d
Weighing ranges	≤ 2	≤ 2	≤ 2
Weighing units	kg	kg	kg
Graduations	1, 2, 5, 10, n	1, 2, 5, 10, n	1, 2, 5, 10, 20, 50
Piece counting with reference	–	–	10, 20, 50, 100, 200
Display, digit height	backlit LCD display, 22 mm	backlit LCD display, 52 mm	backlit LCD display, 55 mm
Additional functions		Totalising, Data Hold function	PRE-TARE function, totalising, Data Hold function, peak hold, zero-point memorisation
WSG load cells	87 - 350 Ω	87 - 1600 Ω	87 - 1600 Ω
Linearisation	2 points	2 points	2-7 points
Input voltage	12 V / 500 mA	12 V / 500 mA	110-230 V AC
Permissible ambient temperature	- 10 °C / 40 °C	0° C / 40° C (not verified) -10° C / 40° C (verified)	-10°C / 40° C (not verified)
Interface RS-232	–	KFN-A01, see page 78	KXS-A04 KXS-A02 (Bluetooth)
Column	–	BFS-A07, see page 109	–
Benchtop stand for display device	yes / yes	yes / yes	yes / yes
Wall mount	–	–	–
Rechargeable battery pack	included	GAB-A04	GAB-A04
Operating/charging time	ca. 45 h / 12 h	ca. 50 h / 12 h	80 h / 12 h
Dimensions Housing WxDxH	195x118x83 mm	266x165x96 mm	232x170x80 mm
Net weight	1 kg	2 kg	2,5 kg

Note: If display devices and platforms (weighing bridges) with EC type approval [M] are combined into a complete unit, this weighing system can be verified in the EU as a class III commercial scale. For further details see page 117.

KERN Pictograms

Internal adjusting (CAL): Quick setting of the balance's accuracy with internal adjusting weight (motordriven).

Adjusting program (CAL): For quick setting of the balance's accuracy.
External adjusting weight required.

Memory: Balance contains memories, e.g. for item data, weighing data, tare weights etc. PLU.

Data interface RS-232: To connect the balance to a printer, PC or network.

RS 485 data interface: To connect the balance to a printer, PC or other peripheral devices. High tolerance against electromagnetic disturbance.

USB data interface: To connect the balance to a printer, PC or other peripheral devices.

Bluetooth data interface: To transfer data from the balance to a printer, PC or other peripheral devices.

Control outputs (optocoupler, digital I/O): to connect relays, signal lamps, valves, etc.

Interface for second balance: for direct connection of a second balance.

Network interface: For connecting the scale to an Ethernet network. With KERN products you can also use a universal RS-232/LAN converter.

GLP/ISO record keeping: of weighing data with date, time and identification-no.
Only with printers from KERN.

Piece counting: Reference quantities selectable. Display can be switched from piece to weight.

Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).

Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays.

Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays. Additional convenient functions, such as barcode and back calculation functions.

Percentage determination: Determining the deviation in % from the target value (100%).

Weighing units: Can be switched to e. g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.

Weighing with tolerance range: Upper and lower limiting can be programmed individually, e.g. dosing/sorting and portioning.

Vibration-free weighing: (Animal weighing program) Vibrations are filtered out so that a stable weight is obtained.

Spray and dust protection IPxx: The type of protection is shown by the pictogram.
For details see the glossary.

Stainless steel: the balance is protected against corrosion.

Suspended weighing: load support with hook on the underside of the balance.

Battery operation: Ready for battery operation. The battery type is specified for each device.

Rechargeable battery pack: rechargeable set.

Mains adapter: 230V/50Hz in standard version for Germany. On request GB, AUS or USA version.

Power supply: integrated in balance. 230V/50Hz in Germany. More standards e. g. GB, AUS, USA on request.

Strain gauges: Electrical resistor on an elastic deforming body.

Tuning fork principle: A resonating body is electromagnetically excited, causing it to oscillate.

Electromagnetic force compensation: Coil in a permanent magnet. For the most accurate weighings.

Single cell technology: Advanced version of the force compensation principle with the highest level of precision.

Verification possible: The time required for verification is specified in the pictogram.

DKD calibration possible: The time required for DKD calibration is shown in days in the pictogram.

Package shipment: The time required to manufacture the product internally is shown in days in the pictogram.

Pallet shipment: The time required to manufacture the product internally is shown in days in the pictogram.

Warranty: The warranty period is shown in the pictogram.

Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight package for your balance, consisting of the test weight, box and DKD certificate, as proof of ist accuracy ... the best pre-requisite for proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E1, E2, F1, F2, M1, M2, M3 with weights from 1 mg - 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe.
(DKD = German Calibration Service)

Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:
- DKD calibration of balances with a maximum load of up to 6 t
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponsing test weight or the calibration service ? Your KERN specialist dealer will be pleased to assist you.

Your KERN specialist dealer: