

TRD

TRD IP65 STAINLESS STEEL PRECISION SCALES SERIES



High resolution IP65 stainless steel balances for industrial and laboratory use. Particularly suitable where there are strict hygiene requirements. The dual range models have a higher accuracy on the lower part of the range. CE-M APPROVED also available.

DIVISION (g): from 0.1 to 1. CAPACITY (g): from 2000 to 12000.

The best solution
for advanced industrial
applications

MAIN FEATURES

- LED display: 7 bright red segments with 7 digits, 15 mm high, for viewing the weight and 6 LEDs for showing the active functions.
- Waterproof keypad with 8 functional keys.
- Stainless steel structure, and plate.
- Functions with aluminium "single point" load cell, with anticorrosive treatments.
- Protection from dust and water splashes according to IP65 standards.
- Adjustable feet and level.
- Digital calibration & set-up configurable from keyboard.
- 12 Vdc power supply with an external 230 Vac power adapter.

SELECTABLE FUNCTIONS:

- Counting
- Totalisation / Formulation with management of 3 zeroable and printable totals independent from each other (partial total, general total, grand total).
- + / - Tolerance check
- Percentage Weigh
- Programmable Set point available for all the functioning modes.

KEYPAD FUNCTIONS:

- Zero, Tare, Print, Mode, On-Off/Clear and 3 navigation keys


I/O SECTION:

- RS232/C or TTL bidirectional output for connection to printer or remote display.
- Bi-directional RS232/C or RS485 configurable output for PC, PLC and additional remote display.

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Internal rechargeable battery
- I/O expansion with 2 inputs and 2 relay outputs (upon price estimate)
- Time/Date or Alibi memory with Time/Date

DETAIL 1



dimensions in mm

VERSIONS

Available versions

Code	Surface l x w (mm)	Max (g)	d (g)	Linearity (g) +/-	CE-M* 2x6000e (g)
TRD6500	190x220	6.500	0,1	0,15	--
TRD10K2	190x220	2.000 / 10.000	0,1/1	0,2/1	--
TRD6DM M	190x220	3.000 / 6.000	--	--	0,5 / 1
TRD12DM M	190x220	6.000 / 12.000	--	--	1 / 2



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI AR GEO
FRANCE sarl
Nogent-sur-Marne
info.fr@diniargeo.com

DINI AR GEO
GMBH
Sinsheim - Germany
info.de@diniargeo.com

DINI AR GEO
UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI AR GEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China
info.cn@diniargeo.com

DINI AR GEO
WEIGHBRIDGES
Calto (RO) - Italy
info@diniargeo.com



HEAD OFFICE

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418 Fax. +39.0536 843521
info@diniargeo.com

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784 Fax. +39.0536 926654
service@diniargeo.com



SALES AND TECHNICAL ASSISTANCE SERVICE