DINI ARGEO
Scales - Weighing systems

MCWK

MCWK "PROFESSIONAL" SERIES STAINLESS STEEL CRANE SCALES



Stainless steel crane scales, with large 40mm DOT LED display, for maximum visibility from any angle and in any light condition, also with direct sunlight. Sturdy and reliable, usable in any environment, inside or outside. Minimum reduction of the lifting space of the crane. IP67 protection, from dust and rain. Available also CE-M APPROVED.
Fitted with test certificate obtained with sample weights.

Working in cooperation with:

SC DATA SPEED SRL

STR DONATH N. 115/33 - 400331 - JUD. CLUJ
Tel. 0040-264566473 Fax. 0040-364-815440
office@cantare.com.ro

The best solution
for advanced industrial
applications

MAIN FEATURES

- Large DOT LED very bright 40mm display, which guarantees a perfect weight visibility from any angle, also from a long distance.
  Usable in any internal or external environment, with good visibility also in full sunlight.
- Adjustable brightness intensity.
- Sturdy structure in STAINLESS steel, with IP67 protection of the load cell and the electronics, against dust and watersprays.
- Fitted with approved upper galvanised shackle and lower swivellng hook.
- Extremely reduced distance between upper shackle and lower hook.
- Precision: +/- 0.03% F.S.
- Waterproof keypad with 5 keys: ZERO, AUTOMATIC TARE, MODE, PRINT and ON/OFF.
- Programmable digital filter, for an excellent weight visualisation in any working condition.
- Programmable turn-off function: automatic, from keypad or from remote control.
- Fitted with radiofrequency 6-key remote control, configurable as only automatic tare or as remote keypad.
- Configurable functioning mode at choice, such as PEAK (maximum read value), HOLD (lock of displayed weight), weighs totalisation, lb/kg conversion (for other available functions see DFW indicator).
- Predisposed for 866MHz radio interface or WiFi, connection to PC, or remote terminal and printer.
- Rechargeable battery, with average life of about 30 hours.
- Predisposed for optional second extractable battery for 24/7 continuous use.
- Fitted with 230 Vac 50 Hz battery charger.
- Digital calibration and Set-Up programmable directly from keyboard or from PC through Dinitools.
- Operating temperature range: -10/+40 ºC.
- Weight: about 25kg (including packing).

AVAILABLE FUNCTIONS FROM REMOTE CONTROL

- Zero; tare; enable / disable function; print; switch-off.

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- RF weight transmission to remote indicator up to over 70m indoors
- WI-FI interface
- Attached thermal printer option box
- Remote weight indicator (see DFW.., 3590.., TRS.., DGT60.. Series' indicators) with printer connected through radio frequency
- ACCREDIA calibration certificate according to OIML/ASTM standards.

VERSIONS

Available versions

Code	Max (kg)	d (kg)	d* HR (kg)	CE-M 3000e (kg)
MCWK6	3000/6000	1/2	0,5/1	--
MCWK6M M	3000/6000	--	--	1/2
MCWK8	6000/8000	2/5	1/2	--
MCWK8M M	6000/8000	--	--	2/5

(*) The HR division is obtainable only with the relative EHR option

www.diniargeo.com



DINI ARGEO FRANCE sarl
Nogent-sur-Marne

DINI ARGEO GMBH
Sinsheim - Germany

DINI ARGEO UK Ltd
Taunton - United Kingdom

DINI ARGEO WEIGHING INSTRUMENTS Ltd
Shanghai - China

DINI ARGEO WEIGHBRIDGES
Calto (RO) – Italy

DINI ARGEO
Scales - Weighing systems

HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy

ISO 9001:2008

SC DATA SPEED SRL

STR DONATH N. 115/33 - 400331 - JUD. CLUJ

Tel. 0040-264566473 Fax. 0040-364-815440

office@cantare.com.ro

SALES AND TECHNCAL ASSISTANCE SERVICE