Pocket balances KERN TEE · TCB · CM · CM-C · TAB



KERN TEE

CAL EXT · BATT · 0.00 TARE · UNIT

1 DAY · 2 YEARS WARRANTY · DKD +3 DAYS

Designer pocket balance at a bargain price

- **Simple and convenient 2-key operation**
- **Cover made of shock proof plastic** as protection against pressure and dust. Can also be used as a tare cup
- **Note: Can be printed with your logo**, from 100 pcs. Please ask for details



KERN TCB

CAL EXT · BATT · 0.00 TARE · UNIT

1 DAY · 2 YEARS WARRANTY · DKD +3 DAYS

This is where the fun starts with pocket format weighing

- **Simple and convenient 2-key operation**
- **Small and handy**
- **Transport box and weighing pan included**
- **Revolving weighing plate** (as overload protection)
- **Note: Individual logo printing on request**



1

KERN CM · CM-C

CAL EXT · BATT · 0.00 TARE · UNIT

1 DAY · 2 YEARS WARRANTY · DKD +3 DAYS

Small, practical and protected in a hard case cover

1 *CM:*

- **Hard case cover as protection against pressure and dust**
- **Integrated calculator**

2 *CM-C:*

- **Hard case cover as protection against pressure and dust**
- **Adjusting weight standard**
- **Draft shield** against air movements standard
- **weighing pan standard**



2



KERN TAB

CAL EXT · BATT · 0.00 TARE · UNIT

1 DAY · 2 YEARS WARRANTY · DKD +3 DAYS

High-precision pocket carat balance for jewellers and travelling salesmen

- **Simple and convenient 4-key operation**
- **Can be switched over from g to ct, gn at the touch of a key**
- **Hard case cover as protection against pressure and dust**
- **Adjusting weight and weighing pan standard**

Model **KERN**	**TEE 150-1**	**TCB 200-1**	**CM 60-2N**	**CM 150-1N**	**CM 320-1N**	**CM 1K1N**	**CM 50-C2N**	**TAB 20-3**
Weighing ranges [Max] g	150	200	60	150	320	1000	10 g | 50 ct	20 g | 100 ct
Readout [d] g	0,1	0,1	0,01	0,1	0,1	1	0,002 g | 0,01 ct	0,001 g | 0,005 ct
LCD display	backlit, digit height 9 mm	digit height 9 mm	digit height 12 mm				digit height 9 mm	backlit, digit height 9 mm
Dimensions of weighing plate	WxD 60x64 mm	Ø 80 mm	WxD 70x80 mm				WxD 50x40 mm	WxD 36x42 mm
Overall dimensions	WxDxH 67x100x22 mm	ØxH 80 mm	WxDxH 85x130x25 mm					WxDxH 95x133x33 mm
Power supply	Batteries included, 2 x 1,5 V AAA	Batteries included, 2 x LR 44 AUTO-OFF function to preserve the battery, can be switched off	Batteries included, 2 x 1,5 V AAA AUTO-OFF function to preserve the battery, can be switched off					Batteries included, 4 x 1,5 V AAA Operating time approx. 150 h
Net weight	100 g	50 g	180 g				200 g	
Permissible ambient temperature	5 °C / 35 °C							10 °C / 30 °C
Option DKD Calibr. Certificate	963-127							

KERN Pictograms

Internal adjusting (CAL): Quick setting of the balance's accuracy with internal adjusting weight (motordriven).

Adjusting program (CAL): For quick setting of the balance's accuracy.
External adjusting weight required.

Memory: Balance contains memories, e.g. for item data, weighing data, tare weights etc. PLU.

Data interface RS-232: To connect the balance to a printer, PC or network.

RS 485 data interface: To connect the balance to a printer, PC or other peripheral devices. High tolerance against electromagnetic disturbance.

USB data interface: To connect the balance to a printer, PC or other peripheral devices.

Bluetooth data interface: To transfer data from the balance to a printer, PC or other peripheral devices.

Control outputs (optocoupler, digital I/O): to connect relays, signal lamps, valves, etc.

Interface for second balance: for direct connection of a second balance.

Network interface: For connecting the scale to an Ethernet network. With KERN products you can also use a universal RS-232/LAN converter.

GLP/ISO record keeping: of weighing data with date, time and identification-no.
Only with printers from KERN.

Piece counting: Reference quantities selectable. Display can be switched from piece to weight.

Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).

Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays.

Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through displays. Additional convenient functions, such as barcode and back calculation functions.

Percentage determination: Determining the deviation in % from the target value (100%).

Weighing units: Can be switched to e. g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.

Weighing with tolerance range: Upper and lower limiting can be programmed individually, e.g. dosing/sorting and portioning.

Vibration-free weighing: (Animal weighing program) Vibrations are filtered out so that a stable weight is obtained.

Spray and dust protection IPxx: The type of protection is shown by the pictogram.
For details see the glossary.

Stainless steel: the balance is protected against corrosion.

Suspended weighing: load support with hook on the underside of the balance.

Battery operation: Ready for battery operation. The battery type is specified for each device.

Rechargeable battery pack: rechargeable set.

Mains adapter: 230V/50Hz in standard version for Germany. On request GB, AUS or USA version.

Power supply: integrated in balance. 230V/50Hz in Germany. More standards e. g. GB, AUS, USA on request.

Strain gauges: Electrical resistor on an elastic deforming body.

Tuning fork principle: A resonating body is electromagnetically excited, causing it to oscillate.

Electromagnetic force compensation: Coil in a permanent magnet. For the most accurate weighings.

Single cell technology: Advanced version of the force compensation principle with the highest level of precision.

Verification possible: The time required for verification is specified in the pictogram.

DKD calibration possible: The time required for DKD calibration is shown in days in the pictogram.

Package shipment: The time required to manufacture the product internally is shown in days in the pictogram.

Pallet shipment: The time required to manufacture the product internally is shown in days in the pictogram.

Warranty: The warranty period is shown in the pictogram.

Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight package for your balance, consisting of the test weight, box and DKD certificate, as proof of ist accuracy ... the best pre-requisite for proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E1, E2, F1, F2, M1, M2, M3 with weights from 1 mg - 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe.
(DKD = German Calibration Service)

Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:
- DKD calibration of balances with a maximum load of up to 6 t
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponsing test weight or the calibration service ? Your KERN specialist dealer will be pleased to assist you.

Your KERN specialist dealer: