Price computing scale KERN RIB



NEW


1


2


3

Application examples
- retail shops
- market places
- farm shops
- pick your own fruit and vegetable sales

Note: Official verification duty for commercial trade

High-quality retail scale with large item memory, user-friendly handling and EC type approval [M]

Features

- 1 KERN RIB-H: **Elevated display backlit,** revolving on column, height of stand approx. 530 mm, must be ordered at purchase
- 2 **Second display** on the rear of the balance
- **Three displays** for weight display (verifiable), reference weight, total weight
- **20 Direct price keys** for frequently recurring article prices
- **Energy management:** Backlight turns off after 5 sec
- **Soil-resistant construction** through water channels at the frame of the housing and sealing rings over the upper housing inlets

Technical data

- Large backlit LCD displays, digit height 18 mm
- Dimensions weighing surface, stainless steel, W×D 294×225 mm
- Overall dimensions W×D×H
  RIB: 340×326×116 mm
  RIB-H: 325×400×400 mm
- Net weight
  RIB-M: approx. 3,2 kg
  RIB-HM: approx. 3,8 kg
- Permissible ambient temperature -10 °C/40 °C

Accessories

- **Protective working cover**, standard, can be re-ordered, scope of delivery: 5 items, KERN RIB-A01S05
- **Rechargeable battery pack internal**, operating time up to 80 h without backlight, charging time approx. 14 h, KERN GAB-A04
- 3 **Tare pan made of stainless steel**, ideal for weighing loose small parts, fruit, vegetables etc., W×D×H 370×240×20 mm, KERN RFS-A02

STANDARD: CAL EXT, MEMORY, UNIT, 230 V, DMS, 1 DAY, 2 YEARS WARRANTY

OPTION: ACCU, DAkkS +3 DAYS

FACTORY: M +3 DAYS

Model KERN	Weighing range [Max] kg	Readout [d] g	Verification value [e] g	Minimum load [Min] g		Options Verification KERN		DAkkS Calibr. Certificate KERN	
Dual-range balance switches automatically to the next largest weighing range [Max] and readout [d].									
RIB 6K-3M	3 | 6	1 | 2	1 | 2	20 | 40		965-228		963-128	
RIB 10K-3M	6 | 15	2 | 5	2 | 5	40 | 100		965-228		963-128	
RIB 30K-2M	15 | 30	5 | 10	5 | 10	100 | 200		965-228		963-128	
with elevated display									
RIB 6K-3HM	3 | 6	1 | 2	1 | 2	20 | 40		965-228		963-128	
RIB 10K-3HM	6 | 15	2 | 5	2 | 5	40 | 100		965-228		963-128	
RIB 30K-2HM	15 | 30	5 | 10	5 | 10	100 | 200		965-228		963-128	

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible.
Verification at the factory, we need to know the full address of the location of use.

KERN Pictograms:

Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven).

Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.

Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.

Alibi memory: Electronic archiving of weighing results, complying with the 2014/31/EU standard.

Data interface RS-232: To connect the balance to a printer, PC or network.

RS-485 data interface: To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.

USB data interface: To connect the balance to a printer, PC or other peripherals.

Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals.

WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals.

Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.

Interface for second balance: For direct connection of a second balance.

Network interface: For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.

Wireless data transfer: between the weighing unit and the evaluation unit using an integrated radio module.

GLP/ISO log: The balance displays the weight, date and time, regardless of a printer connection.

GLP/ISO log: With weight, date and time. Only with KERN printers.

Piece counting: Reference quantities selectable. Display can be switched from piece to weight.

Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).

Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.

Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition.

Totalising level A: The weights of similar items can be added together and the total can be printed out.

Percentage determination: Determining the deviation in % from the target value (100 %).

Weighing units: Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.

Weighing with tolerance range: Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning.

Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value.

Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.

ATEX explosion protection: Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device.

Stainless steel: The balance is protected against corrosion.

Suspended weighing: Load support with hook on the underside of the balance.

Battery operation: Ready for battery operation. The battery type is specified for each device.

Rechargeable battery pack: Rechargeable set.

Universal mains adapter: with universal input and optional input socket adapters for
A) EU, GB
B) EU, GB, CH, USA
C) EU, GB, CH, USA, AUS

Mains adapter: 230V/50Hz in standard version for EU. On request GB, USA or AUS version available.

Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request.

Weighing principle: Strain gauge Electrical resistor on an elastic deforming body.

Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate.

Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings.

Weighing principle: Single cell technology Advanced version of the force compensation principle with the highest level of precision.

Verification possible: The time required for verification is specified in the pictogram.

DAkkS calibration possible (DKD): The time required for DAkkS calibration is shown in days in the pictogram.

Package shipment: The time required for internal shipping preparations is shown in days in the pictogram.

Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram.

Warranty: The warranty period is shown in the pictogram.

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAkkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe.
Thanks to the high level of automation, we can carry out DAkkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:
- DAkkS calibration of balances with a maximum load of up to 50 t
- DAkkS calibration of weights in the range of 1 mg – 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer:

*The *Bluetooth*® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.