
Pallet scale KERN UFC




3

Limited tare range with verifiable models (1/6 from [Max])

! Shipment via freight forwarder. Please ask for dimensions, gross weight, shipping costs

Pallet scale with steel load support (IP67) and stainless steel display device (IP65), with EC type approval [M]

Features

- **High mobility:** thanks to rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations
- 1 **Load support:** steel, lacquered, protection against dust and water splashes (IP67), 4 silicone-coated stainless load cells. Also available as component without the display device, KERN KFU-V20, see page 152
- **2 rollers and handle** for easy transport of the scale
- 2 **Display device: KERN KFN-TM**, details see page 148
- **Weighing with tolerance range (checkweighing):** A visual and audible signal assists with portion division, dispensing or grading or the rapid checking of items on palettes
- Counting system: A counting scale can be connected using the data interface, and this can be used to create a high-capacity counting system for counting the very small parts in largest quantities
- **Totalising** of weights and piece counts

Technical data

- Large backlit LCD display, digit height 52 mm
- Dimensions of display device WxDxH 266x165x96 mm
- Cable length of display device approx. 5 m
- Net weight approx. 52 kg
- Permissible ambient temperature -10 °C / 40 °C

Accessories

- 3 **Stand** to elevate display device, height-adjustable, height of stand 750-1000 mm, KERN BFS-A07
- **Rechargeable battery pack internal**, operating time up to 35 h without backlight, charging time approx. 12 h, KERN GAB-A04
- **Data interface RS-232**, interface cable included, must be ordered at purchase, KERN KFN-A01
- **Y-cable** for parallel connection of two terminal devices to the RS-232 interface on the scale, e.g. signal lamp and printer, KERN CFS-A04
- **Signal lamp** for visual support of weighing with tolerance range, only in combination with data interface KERN KFN-A01, for details see page 181, KERN CFS-A03
- **Large display** with superior display size, digit height 76 mm, WxDxH 541x55x180 mm, details see page 181, KERN YKD-A02
- **Cable with special length** 15 m, between display device and platform, must be ordered at purchase, KERN BFB-A03
- **Suitable printers** see page 177 ff.

STANDARD: CAL EXT, RS 232, PCS, SUM, TOL, MOVE, IP 65 (2), IP 67 (1), MULTI, DMS, 5 DAYS, 3 YEARS WARRANTY

OPTION: DAkkS +3 DAYS

FACTORY: RS 232, ACCU, M +3 DAYS

Model KERN	Weighing range [Max] kg	Readout = Verification value [d] = [e] kg	Minimum load [Min] kg		Options Verification KERN		DAkkS Calibr. Certificate KERN	
UFC 600K-1M	600	0,2	4		965-230		963-130	
UFC 1T-1M	1500	0,5	10		965-230		963-130	

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.

KERN Pictograms:

Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven).

Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.

Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.

Alibi memory: Electronic archiving of weighing results, complying with the 2009/23/EC standard.

Data interface RS-232: To connect the balance to a printer, PC or network.

RS-485 data interface: To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.

USB data interface: To connect the balance to a printer, PC or other peripherals.

Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals.

WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals.

Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.

Interface for second balance: For direct connection of a second balance.

Network interface: For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.

Wireless data transfer: between the weighing unit and the evaluation unit using an integrated radio module.

GLP/ISO log: The balance displays the weight, date and time, regardless of a printer connection.

GLP/ISO log: With weight, date and time. Only with KERN printers.

Piece counting: Reference quantities selectable. Display can be switched from piece to weight.

Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).

Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.

Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, adjustment of recipe when dosages are exceeded, multiplier function, barcode.

Totalising level A: The weights of similar items can be added together and the total can be printed out.

Totalising level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, adjustment of recipe when dosages are exceeded, multiplier function, barcode recognition.

Percentage determination: Determining the deviation in % from the target value (100 %).

Weighing units: Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.

Weighing with tolerance range: Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning.

Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value.

Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.

ATEX explosion protection: Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device.

Stainless steel: The balance is protected against corrosion.

Suspended weighing: Load support with hook on the underside of the balance.

Battery operation: Ready for battery operation. The battery type is specified for each device.

Rechargeable battery pack: Rechargeable set.

Universal mains adapter: with universal input and optional input socket adapters for
A) EU, GB
B) EU, GB, CH, USA
C) EU, GB, CH, USA, AUS

Mains adapter: 230V/50Hz in standard version for EU. On request GB, USA or AUS version available.

Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request.

Weighing principle: Strain gauge Electrical resistor on an elastic deforming body.

Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate.

Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings.

Weighing principle: Single cell technology Advanced version of the force compensation principle with the highest level of precision.

Verification possible: The time required for verification is specified in the pictogram.

DAkkS calibration possible (DKD): The time required for DAkkS calibration is shown in days in the pictogram.

Package shipment: The time required for internal shipping preparations is shown in days in the pictogram.

Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram.

Warranty: The warranty period is shown in the pictogram.

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2000 kg. In combination with a DAkkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe.
Thanks to the high level of automation, we can carry out DAkkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:
- DAkkS calibration of balances with a maximum load of up to 50 t
- DAkkS calibration of weights in the range of 1 mg – 2500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages D, GB, F, I, E, NL, PL

Your KERN specialist dealer:

*The *Bluetooth*® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license.
Other trademarks and trade names are those of their respective owners.